

FULLY INTERLOCK FLEXIBLE CONDUIT



FULL INTERLOCK · HIGHER MECHANICAL STRENGTH

In Fully InterLock tubing, the strip edges are completely interlocked. This construction provides increased crush protection and higher axial strength for heavy-duty and long-distance cable protection.

Typical applications: heavy machinery, railways, marine equipment, chemical plants, security systems and outdoor installations.

STANDARD SPECIFICATIONS

TYPE	INCH	I.D. (mm)	O.D. (mm)	O.D. + SHEATH (mm)	PACKING (m)
S2S1	—	4.0	6.0	7.0	100
S2S1	—	4.6	6.6	8.0	100
S2S1	—	5.0	7.0	8.0	100
S056090C2S1	—	5.4	7.8	9.0	100
S060092C2S1	—	6.0	8.0	9.2	100
S063100C2S1	1/4	6.3	8.4	10.0	100
S070900C2S1	—	7.0	9.0	10.0	100
S080100C2S1	—	8.0	10.2	11.2	100
S2S1	3/8	9.5	12.0	15.0	50
S2S1	—	10.0	12.5	15.0	50
S2S1	1/2	12.7	15.5	17.7	50
S2S1	—	16.1	18.5	20.5	50
S2S1	3/4	20.8	24.3	26.7	40
S2S1	—	22.0	25.7	28.0	40
S2S1	1	26.0	30.0	33.0	30
S2S1	1-1/4	34.0	39.0	42.2	30
S2S1	1-1/2	39.0	44.0	47.8	20
S2S1	2	51.0	56.0	59.4	10