

SQUARELOK FLEXIBLE CONDUIT



CONSTRUCTION

SquareLok tubing is formed from a continuous stainless-steel strip. One profile leg locks over the adjacent profile, providing high flexibility and a small bend radius for tight spaces and continuous flexing.

Applications: robotics, automation equipment, precision optics, medical endoscopes, sensor cables and data wiring.

STANDARD SPECIFICATIONS

TYPE	INCH	I.D. (mm)	O.D. (mm)	O.D. + SHEATH (mm)	PACKING (m)
P040070S2D1	—	4.0	6.0	7.0	100
P046080S2D1	—	4.6	6.6	8.0	100
P050080S2D1	—	5.0	7.0	8.0	100
P006095S2D1	—	6.0	8.0	9.2	100
P062940S2D1	1/4	6.4	8.4	9.4	100
P070100S2D1	—	7.0	9.0	10.2	100
P080110S2D1	—	8.0	10.2	11.2	50
P010140S2D1	3/8	10.0	13.0	14.2	50
P125177S2D1	1/2	12.7	16.0	17.7	50
P161213S2D1	—	16.1	19.8	21.3	50
P208267S2D1	3/4	20.8	24.3	26.7	40
P260330S2D1	1	26.0	30.0	33.0	30
P340422S2D1	1-1/4	34.0	39.0	42.2	30
P390478S2D1	1-1/2	39.0	44.0	47.8	20
P510594S2D1	2	51.0	56.0	59.4	10